

# DA DO

Ceiling

**TYPE:**

**PROJECT NAME:**

MODEL #

FINISH

LED COLOR

OPTIC

DRIVER

VOLTAGE



# DA DO

Marco Pagnoncelli - 2012

Faretto da soffitto con corpo in alluminio.

Fornito con LED 120V che non necessita di alimentatore.

Finiture colori:

verniciato bianco (BI), verniciato nero (NE), verniciato moka (MK), alluminio satinato (AL).

Disponibile nella temperatura colore LED 3000 °K e 2700 °K.

Classe energetica A++, A+, A

Modello depositato



Ceiling spotlight with aluminium body.

Supplied with 120V LEDs not requiring a power supply unit.

Available in:

white varnish (BI), black varnish (NE), mocha varnish (MK), brushed aluminium (AS). Available with 3000 °K or 2700 °K LED colour temperature.

**TRIAC Dimming - Works with most of the existing TRIAC dimmers.**

Energy class A++, A+, A

Registered design

## FINISH

BI = WHITE

NE = BLACK

MK = MOCHA

AS = BRUSHED ALUMINIUM

BI



NE



MK





AS



INSTALLATION OPTIONS: Please Select One of the Installation Options Below

○ - Installation Option 1: With no backplate for a clean installation with a plaster ring

○ - Installation Option 2: With Visual 4" x 4" SQUARE BACKPLATE



| Art.    | W   | V   | Lumen | °K Led | A cm  | B cm  | C cm  |
|---------|-----|-----|-------|--------|-------|-------|-------|
| DADO1.5 | 4,5 | 120 | 350   | 3000   | 5(2") | 5(2") | 5(2") |

INPUT VOLTAGE 120V