

SPILLO

Wall/Ceiling

TYPE:

PROJECT NAME:

MODEL #

FINISH

LED COLOR

OPTIC

DRIVER

VOLTAGE



SPILLO

Marco Pagnoncelli - 2012

Lampada da parete realizzata in trafilata di ottone sezione 7x7 mm.
Disponibile in 2 misure e potenze.
Illuminazione a microstriscia LED ad alta efficienza luminosa.
Completa di alimentatore.
Finiture colore:
verniciato bianco (BI), verniciato nero (NE), cromo (CR), foglia oro+oro (FO+OR).

Classe energetica A++, A+, A

Modello depositato

Wall lamp in drawn brass rod, 7x7 mm section.
Available in 2 dimensions and power levels.
Lighting by high luminous efficiency LED micro-strip.
Complete with power supply unit.
Available in:
white varnish (BI), black varnish (NE), chrome (CR), gold leaf+gold (FO+OR).


TRIAC Dimming - Works with most of the existing TRIAC dimmers.

Energy class A++, A+, A

Registered design

FINISH

BI = WHITE
NE = BLACK
CR = CHROME
FO = GOLD LEAF
OR = BRUSHED GOLD



| Art. | W | V | Lumen | °K led | A cm | B cm | C cm | D cm | E cm | F cm | |
|-------------|------|----|-------|--------|-----------|---------|-----------|-----------|----------|------------|-----------------|
| SPILLO.50.Q | 5,28 | 12 | 440 | 3000 | 50(19.7") | 3(1.2") | 4,5(1.8") | 5,5(2.2") | 12(4.7") | 10,5(4.1") | Integral driver |
| SPILLO.70.Q | 7,92 | 12 | 660 | 3000 | 70(27.6") | 3(1.2") | 4,5(1.8") | 5,5(2.2") | 12(4.7") | 10,5(4.1") | Integral driver |

INPUT VOLTAGE 120V

INSTALLATION NOTE: Comes with 4" x 4" SQUARE BACKPLATE to cover the junction box

