

TULIPANO

Suspension

TYPE:

PROJECT NAME:

MODEL #

FINISH

LED COLOR

OPTIC


DRIVER

VOLTAGE




Lampada a sospensione a luce diretta e indiretta a forma tronco conica in gesso con bassorilievi floreali interni bianchi. Struttura in alluminio da 5 mm laccata bianco collegata al rosone tramite una cordina d'acciaio di 2,5 mm. Cavo elettrico incolore predisposto per accensione separata tra luce superiore ed inferiore. Illuminazione a risparmio energetico. Chiusura lampadine con disco in policarbonato opalino. Finiture: bianco opaco laccato a liquido+bianco lucido (BI), testa di moro opaco+bianco (TM+BI), foglia oro+bianco (FO+BI), foglia argento+bianco (FA+BI).

Direct and indirect-light suspension lamp in truncated cone shape, made in plaster with white internal floral bas-relief work. Structure in 5 mm aluminium with white enamel finish, linked to the ceiling plate by a 2.5 mm steel cable. Colourless electrical cable providing separate control of upper and lower light sources. Low-consumption light source. Bulbs protected by a disc in opal methacrylate. Available in: matt white liquid enamel+gloss white (BI), matt dark brown+ white (TM+BI), gold leaf+ white (FO+BI), silver leaf+ white (FA+BI).



Art.	W	V	Attacco/Socket	A cm	B cm	C cm
TULIPANOSP	2+2x36	220	TC-L 2G11	Ø62(24.4")	47(18.5")	max 170(66.9")
TULIPANOSG	2+2x55	220	TC-L 2G11	Ø87(34.2")	69(27.2")	max 190(74.8")



Classe energetica. Energy class.



FA+BI